

REDLINE VERSION OF THE ORIGINAL
SPECIFICATION SHOWING PROPOSED
AMENDMENTS

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235

METHOD AND APPARATUS FOR WELDING SHEET OVERLAPS

BACKGROUND OF THE INVENTION

5 1. Technical Field

The present invention relates to methods and apparatus for welding sheet metal in general,
and in particular to automated methods and apparatus for welding discrete sheet metal bodies.

2. Background Information

~~The invention relates to a method according to the introductory part of Claim 1. The~~
~~invention also relates to a welding apparatus according to the introductory part of Claim 11.~~

It is known to weld sheet overlaps with welding rollers, especially with the aid of intermediate wire electrodes, such as in the welding of can bodies for example. A problem that arises especially when articles are welded individually, in particular can bodies where each body impinges individually on welding rollers in the horizontal position, as may be the case on manual welding machines or automatically fed welding machines, is that of welding the initial weld point at the start of the can body or other article to be welded. Because the welding energy or heat introduced at that point can only diffuse in one direction along the line of the seam, application of the full rated welding current for welding the overlapping seam at the initial point results in burning, or a defective welded joint. It is therefore known in the state of the art to reduce the welding current initially, as indicated in the schematic time/current diagram of Figure 1. Accordingly, on the welding machine, the welding AC voltage or current and the drive to the welding rollers and/or wires are activated at a time Pt. 1 with the welding current source impressing a reduced welding current with a current value A

which is lower than the rated current value B for the overlapping seam. The welding current 1 may for example be a 50 Hz alternating current.

At a time Pt. 2, the travel carriage of the welding machine, which carries the article to be welded e.g. a can body 2, reaches a predetermined position in front of the welding rollers, whereupon a time interval t_1 commences at the end of which the rated current value B is impressed at the electrode wires by the welding current source. The article, in this case the body 2, reaches the electrode wires at a random point in time with respect to the welding current 1, e.g. as shown, when the current half-wave is at its peak, and welding commences at the reduced current A and changes over to the rated current B after the time interval t_1 . It is also known to lower the current towards the back end of the article, e.g. to the value C, as the back end of the article or can body has already been heated by a forward diffusion of heat through the article or body. In Figure 1 this is indicated by time Pt. 3, the start of a time interval t_2 governed by the position of the carriage and effecting a reduction of the current to the value C at the back end of the welded article. After the welded article has run through, the movement of the rollers and/or wires is stopped, and the welding current switched off, at time Pt. 4. Figure 2 shows this known process for the case where coated, e.g. zinc galvanized, leaded, or aluminized, sheets are to be welded. These require higher welding currents than uncoated sheets, because of the presence of the coating. The higher welding current if applied as an uninterrupted alternating current can cause burning, and for this reason it is known to activate the welding current in bursts and to provide pauses between bursts (the so-called "stitch weld" process). Figure 2 shows such a process with a current/pause ratio of 2:1 as an example. In other respects the conditions are the same as in Figure 1: Pt 1 is the starting-point for the movement of the wires and the impression of the

reduced current A, Pt. 2 defines the starting-point for the time interval t_1 , and is triggered by the position of the carriage, and at the end of t_1 the rated current value B is impressed. Time Pt. 3, again governed by the position of the carriage, initiates the time interval t_2 , which triggers the reduction of the current to the final value C, and at time Pt. 4 the machine is stopped. Usually when the reduction is made to the current value C there is a changeover to uninterrupted alternating current, as shown in Figure 2. Again in the case of the stitch weld process, the point on the current curve at which the leading edge of the article to be welded impinges on the welding rollers and/or electrode wire is undefined. In Figure 2 this is shown as happening by chance at the point where the welding current passes through zero, but it could happen anywhere within a welding current burst or a welding current pause. Thus, although it is true that in the state of the art the initial weld point is welded at reduced current A, the weld quality at the initial point may vary. When the leading edge of the article to be welded impinges on an intermediate wire electrode that is already live, and therefore hot, a wire break may occur, especially if at that moment the intermediate wire electrode is being subjected to a peak current level (Figure 1). The electrode is particularly susceptible to such damage when thick sheets, with a thickness of e.g. 0.5 to 1.25 mm, are being welded, where with a single overlap the material to be welded has twice the thickness, and with a folded or doubled overlap, four times the thickness.

DISCLOSURE OF THE INVENTION

Therefore a fundamental problem of the invention is to provide a method for welding sheet overlaps, particularly in thick sheets, that does not have the stated drawbacks.

For a method of the kind stated at the outset, this problem is solved by the
 5 ~~characterizing features of Claim 1: a method for welding an overlapping article of sheet metal on a welding apparatus that includes welding electrode rollers, wherein welding current is not applied to the welding electrodes until the article to be welded is between the electrodes.~~

By deliberately not applying welding current to the electrodes until the article to be welded is between the welding electrodes, the drawbacks can be overcome. It has been found
 10 that welding problems at the initial point and breaks in the wire no longer occur. By adopting this measure, it is even possible to dispense with the initial reduction in welding current, so that welding is performed with the rated welding current value preferably from the start.

Preferably, the moment of switching-on is derived from the deflection of an electrode roller, preferably the upper electrode roller. This gives a particularly reliable indication of the
 15 actual position of the leading edge of the article between the electrodes.

A further fundamental problem of the invention is to provide a welding apparatus that does not have the stated drawbacks.

For a welding apparatus of the kind stated at the outset, this problem is solved by the
 characterizing features of Claim 11:

20 a welding apparatus that includes welding electrode rollers, a welding current source, controllable switch arrangement, a control device, and a switch means. The welding current source is connected to the welding electrodes by the controllable switch arrangement, and the control device controls the switch arrangement. The switch means, which is connected to the

control device, is triggered by the position of the forward or rear edge of the article to be welding via the welding electrode rollers. The control device is configured to receive from the switch means a signal indicating the position of the edge of the article to be welded with respect to the electrode rollers and in dependence thereon to deliver to the switch arrangement
5 a signal releasing the welding current to the electrode rollers and/or the intermediate wire electrodes.

These and other objects, features and advantages of the present invention will become apparent in light of the detailed description of the invention, and the accompanying drawings.

10 BRIEF DESCRIPTION OF THE DRAWINGS

The state of the art and examples of ways of carrying out the invention will now be described in detail with reference to the figures, in which

Figure 1 is a schematic diagram of the welding current curve in relation to the position of an article to be welded, according to the state of the art;

15 Figure 2 is a similar state-of-the-art diagram to Figure 1 showing welding current for stitch welding;

Figure 3 is a schematic diagram of the welding current curve according to one way of carrying out the invention;

20 Figure 4 is a schematic view of the electrodes and controls of a welding apparatus to elucidate the invention;

Figure 5 is a partial view of a welding apparatus according to one embodiment of the invention; and

Figure 6 is a top view of the setting disk for sheet thickness.

DETAILED DESCRIPTION OF THE INVENTION

Figure 1 shows the curve of welding current 1 that has already been described for welding a can body 2 in accordance with the state-of-the-art. Figure 2 shows the fundamentally similar curve of current in the stitch weld process as already described in the introduction.

Figure 3 shows, in the same mode of representation, the curve over time of the welding current 3, 4, over a can body 2 as welded article. At time Pt. 1' the drive to the electrode rollers and/or wires is started, as is known in principle and as need not be further described here. However, the electrodes still carry no voltage or current. The welding voltage/current is not switched through to the electrodes until time 2', when the article or can body 2 has passed between the electrode rollers and wires. This preferably takes place at the passage through zero as shown in Figure 3. Surprisingly, it has been found that by adopting this measure it is even possible for the initial reduction in current to be abandoned altogether (though the reduction can of course still be made as before). Preferably, as shown in Figure 3, welding is performed with the rated current value B from the outset. To obtain a weld of high quality, it is moreover preferred that welding be initially performed with uninterrupted alternating current e.g. for a segment of seam length of 5 to 30 mm, particularly 10 to 20 mm, and especially approx. 15 mm. Thereafter a changeover can be made, as shown, to the stitch weld process with individual bursts 4 of welding current, as known from the state-of-the-art. But it is also possible to continue welding with uninterrupted alternating current; the choice will depend on the type of sheet, as already known in the state-of-the-art. The end of the

welding is no different from the state-of-the-art, and the remarks made on the state-of-the-art with regard to the times Pt.3 and Pt. 4 and time interval t2 still apply.

To carry out the method, it is important to detect the position of the article or can body so that the welding current from the current source is applied just as the article being

5 conveyed in the welding direction arrives between the electrodes, so that the initial point can be welded with the welding current which is then applied. The moment for switching one, or for applying the current, is therefore preferably derived from the position of the article itself, not from the device conveying it to the welding rollers. In particular, it is derived from the leading edge of the article, or from the trailing edge if the length of the article is known. If

10 the position of the edge is detected at a predetermine point ahead of the welding rollers, e.g. by a light barrier, then provided that the rate at which the article for welding is being fed by the conveyor device of the apparatus is known, the moment when the article is located between the electrodes, so that the initial welding point must be set by switching on the welding current, is known. Hence the control device 20 (Figure 4) of the welding apparatus

15 can determine the moment for switching-on Pt. 2' from the edge position signal and the rate of feed, and possibly also the length of the article to be welded. Preferably, however, the moment for switching-on is derived from the deflection of the welding rollers, and in particular of the upper welding roller if the lower welding roller is fixed. The deflection of the welding roller gives a direct indication of the desired position of the article between the

20 welding rollers. This indication can be fed to the control device of the welding apparatus, so causing welding current to be applied to the electrodes.

Figure 4 shows a schematic view of a welding apparatus 6 to elucidate this process, and Figure 5 shows a corresponding detail view of part of the welding apparatus. In Figure 4

a welding apparatus 6, with a lower welding electrode roller 8 and upper welding electrode roller 7, which is being used to weld an article 2, is shown; the article 2 is being conveyed between the welding rollers 7, 8 by a conveyor device which is not shown, e.g. a travel carriage.

5 The lower welding roller 8 is arranged in a known manner on a welding arm 10 which is surrounded by the article 2 to be welded. Preferably an intermediate wire electrode 12, which in a known manner is guided in the welding machine and forms a constantly replenished welding electrode, is provided on the lower welding roller 8. The same applies to the upper welding roller 7 provided with the intermediate wire electrode 11 of which, as in the case of the lower intermediate wire electrode 12, only a small portion is shown. The upper welding roller 7 is arranged on an upper arm 9 which is pivotable about the axis 24. The lower welding roller 8 and its welding arm 10 are usually fixedly mounted, and the upper welding arm 9 together with the roller 7 can be pressed against the lower welding roller 8 by an actuating device 29 (Figure 5) to apply the necessary welding force. This actuating device permits an elastic upward tilt in the direction of the arrow D (Figure 4) on insertion of the article 2 between the welding rollers. Preferably, this deflection of the upper welding roller is detected in order to derive a signal which indicates that the article 2 for welding is between the welding rollers 7 and 8. Figure 4 shows an electric switch 21 provided for this purpose, whose actuating element 21' is operated by an actuating member 22 adjustably mounted at the top of the welding arm, when the welding roller moves upwards in the direction D and the upper end of the welding arm 9 moves in the direction of the arrow E. The actuating member 22 is adjustably arranged at the top end of the arm 9 so that the actuating element 21' is operated only beyond a predetermined deflection which is dependent on the thickness of the

overlap, or the actual sheet thickness of the article 2 to be welded. When actuation of the switch 21 by deflection of the upper welding roller transmits a signal to the control device 20, the latter in turn transmits an activation signal via the signal path 29 to the switch element 17, which applies the welding current from a welding current source 14 via leads 15, 16 and 18 to the welding electrodes. The welding current source 14 is preferably controllable so that the amplitude and frequency of the welding current B can be adjusted by means of the control device 20. The switch element 17 is preferably such an element, which switches the welding current/voltage only at a passage through zero. Such switches are well known in electronics, and will not be described further here. In the way which has been indicated, the welding current curve can be generated by the method so that welding current is not applied to the welding electrodes until the article to be welded is between the welding electrodes.

Figure 5 shows a more accurate representation of the upper part of the welding machine with the upper welding roller 7 and the welding arm 9, which is able to pivot on the machine frame about a fixed pivot axis 24. Current is supplied to the upper welding roller via a bus bar 18. The actuating member 29 serves to press the upper welding roller 7 elastically against the article to be welded and to tilt the roller 7 away to load the welding machine with the article to be welded. The switch 21 with its actuating element 21' is also mounted on the machine frame. At the upper end 23 of the welding arm 9, the adjusting member 22 is again shown. By means of this adjusting member 22, a basic setting can be made for the actuation of the switch 21 upon upward deflection of the welding roller 7. A further setting element 26 which is interposed between the adjusting means 22 and the actuating element 21' of the switch 21 is provided for adaptation to the varying sheet thicknesses of different articles. This setting element 26 is preferably a disk with regions of different thickness which can be

inserted between the adjusting element 22 and the actuating element 21' to suit the thickness of the sheet metal. It may for example be a rotatable disk 26 with pockets 27 machined to different depths so that the residual thickness of the disk, which is placed between the parts 22 and 21', can be matched to different specified sheet-metal thicknesses.

5 Figure 6 shows a corresponding circular disk 26 with six different pockets 27 each marked with the corresponding single sheet thickness. The disk 26 is mounted rotatably about an axle 28 on the machine frame so that each of the pockets 27 can be brought into engagement between the parts 22 and 21' simply by turning the disk, the residual thickness of the disk in the region of the pocket then directly determining the deflection of the welding roller 7 at which the switch 21 is thereby actuated. Thus the welding machine operator has only to press the disk 26 in the direction of the arrow E against the spring 28' arranged around the axle 28 in order to free the disk 26 for turning, and rotate the disk so that the pocket showing the specified sheet thickness engages between the parts 22 and 21'. The disk 26 is then pushed forwards again towards the element 22 by the spring 28', and the element 21' is also restored by the spring of the switch 21 to the position shown in Figure 5. In this way, adaptation can easily be made to the specific thickness of sheet material of the article to be welded.

10
15
20 Although this invention has been shown and described with respect to the detailed embodiments thereof, it will be understood by those skilled in the art that various changes in form and detail thereof may be made without departing from the spirit and the scope of the invention.

What is claimed is:

1. Method for welding an overlapping article (2) of sheet metal on a welding apparatus (6) with welding electrode rollers (7, 8) and if required with additional intermediate wire electrodes (11, 12), characterized in that the welding current (3) (3) is not applied to the electrodes until the article to be welded is between the electrodes.

5

2. Method according to Claim 1, characterized in that the moment (Pt. 2') of switching on the welding current (3) is derived from the forward or rear edge, in the welding direction, of the article to be welded.

10

3. Method according to Claim 2, characterized in that the moment of switching on is derived from the forward edge by detecting the deflection of at least one of the welding electrode rollers upon insertion of the article between the welding electrode rollers.

15

4. Method according to Claim 3, characterized in that the welding current is applied to the welding electrode rollers at the next passage through zero of the said current following a predetermined, adjustable deflection of the said rollers.

20

5. Method according to ~~any one of Claims 1 to 4~~, characterized in that the rated welding current value (B) for the overlapping weld seam is impressed at the welding electrode rollers and/or intermediate wire electrodes at the moment of switching on.

6. Method according to ~~any one of Claims 1 to 4~~, characterized in that a rated welding current value (A) lower than the rated welded current value (B) for the overlapping weld seam is impressed at the welding electrode rollers and/or intermediate wire electrodes at the moment of switching on and the rated current value (B) is impressed after a predetermined time.

5

7. Method according to ~~any one of Claims 1 to 6~~, characterized in that the welding current is applied to the welding electrode rollers and/or intermediate wire electrodes as a steady alternating current at the moment of switching on and is applied thereto as alternating current interrupted by pauses after a predetermined time.

10

8. Method according to ~~any one of Claims 1 to 7~~, characterized in that the articles to be welded are can bodies-(2).

15

9. Method according to ~~any one of Claims 1 to 8~~, characterized in that the article to be welded (2) has a single or double overlap-(30, 31).

10. Method according to ~~any one of Claims 1 to 9~~, characterized in that the single sheet thickness of the articles to be welded is 0.4 mm to 1.25 mm, and in that the articles to be welded comprise in particular coated sheets.

20

11. ~~Welding~~ A welding apparatus with welding electrode rollers ~~(7, 8)~~ and if required with additional intermediate wire electrodes ~~(11, 12)~~, with a welding current source ~~(14)~~, in particular an AC welding current source, that can be connected to the electrodes by a controllable switch arrangement ~~(17)~~, and with a control device ~~(20)~~ for the switch arrangement, characterized in that a means ~~(21)~~ connected to the control device is provided which is triggered by the position with respect to the welding electrode rollers of the forward or rear edge, viewed in the welding direction, of an article to be welded, and in that the control device ~~(20)~~ is configured to receive from the means ~~(21)~~ a signal indicating the position of the edge of the article to be welded with respect to the electrode rollers and in dependence thereon to deliver to the switch arrangement ~~(17)~~ a signal ~~(29)~~ releasing the welding current to the electrode rollers and/or the intermediate wire electrodes.

12. ~~Welding~~ A welding apparatus according to Claim 11, characterized in that the means is configured to detect the deflection or at least one of the welding electrode rollers ~~(7)~~ by the article ~~(2)~~ passing between the electrodes.

13. Welding apparatus according to Claim 11 ~~or Claim 12~~, characterized in that the means for detecting the deflection comprises a setting arrangement ~~(22, 26, 27, 28)~~ by means of which the response to the position of the leading edge of the article to be welded is adaptable to the thickness of the sheet metal.

14. Welding apparatus according to Claim 13, characterized in that the setting arrangement has a disk (26) with a plurality of regions (27) of different thickness in a predetermined proportion to the thickness of the sheet material of the articles to be welded.

5 15. Welding apparatus according to Claim 14, characterized in that the disk (26) is rotatably arranged, and the regions (27) are recesses of different depth in the disk which are preferably each marked with the corresponding thickness of the sheet material of the article to be welded.

10 16. A method for welding a sheet metal article along an overlapping seam, comprising the steps of:

providing a welding apparatus having electrode rollers, wherein the welding apparatus selectively provides welding current to the electrode rollers;

inserting the sheet metal article between the rollers prior to welding current being provided to the electrode rollers;

determining the presence of the sheet metal article between the electrode rollers; and

providing welding current to electrode rollers if it is determined the sheet metal article is between the welding electrodes, thereby welding the sheet metal article.

17. The method of claim 16, wherein the step of determining the presence of the sheet metal article between the electrode rollers includes determining the position of one or both of a leading edge or a trailing edge of the article to be welded;
wherein the welding current is provided to the electrode rollers when it is determined that the leading edge of the article is positioned between the welding electrodes.

18. The method of claim 17, wherein the step of determining the presence of the sheet metal article between the electrode rollers includes sensing the movement of one of the electrode rollers, wherein when one of the rollers is moved a predetermined distance, the welding current is provided to the electrode rollers.

19. An apparatus for welding sheet metal articles, comprising:

at least two electrode rollers;

a welding current source;

a controllable switch arrangement for selectively providing welding current from the welding current source to the at least two electrodes; and

a switch means for signaling the presence of one of the sheet metal articles between the electrode rollers, wherein the switch means has a first signal output when one of the sheet metal articles is disposed between the electrode rollers, and a second signal output when none of the sheet metal articles are disposed between the electrodes;

wherein the switch means changes from the second signal output to the first signal output when an edge of the sheet metal article is disposed between the electrode rollers.

20. The apparatus of claim 19, wherein the switch means includes a pivotally mounted arm for mounting one of the at least two electrode rollers, wherein inserting the edge of the sheet metal article to be welded causes the arm and mounted roller to pivot away from another of the at least two electrode rollers.

Abstract ABSTRACT OF THE DISCLOSURE

Where can bodies of sheet metal are welded between the welding rollers of a welding machine, the welding current (3) is not applied to the welding rollers until the body (2) is
5 between the welding electrode rollers. In this way, the quality of the weld at the initial weld point is improved, and where intermediate wire electrodes are used, wire breaks are reliably prevented.




FIG. 1
State of the Art




FIG. 2
State of the Art






FIG. 3






FIG. 5

[illegible]